

Marson Rivets, Inserts & Installation Tools



marson
rivets

Table of Contents

Introduction	2
General Information.....	3,4
Design Information	5,6
Steel Rivets	7,8
Aluminum Rivets	9,10
Aluminum/Steel Rivets	11,12
Stainless Rivets	13
Stainless/Steel Rivets.....	14
Closed-End Rivets	15
Multi-Grip Rivets	16
Copper/Brass Rivets.....	17
Copper/Steel Rivets	17
Tri-Bulb Rivets	17
Painted Rivets.....	18
Back-Up Washers.....	18
Steel Q-Lok Rivets	19
T-Rivets/Klik-Split®	19
Automotive/Special Application Rivets.....	20
Klik-Lok™ Rivets.....	21,22,23,24
Plastic Rivets	25,26
Plastic Rivet Tools.....	27
Hand Rivet Tools and Kits.....	28,29,30
Air/Hydraulic Rivet Tools	31
Riveter Capacity Chart	32
Air/Hydraulic Tool Dimensions	33
Air/Hydraulic Tool Specifications	33
Threaded Insert Tools and Kits	34,35
Klik Rivet-Nuts.....	36
Klik Poly-Nuts	37
Klik Thread-Serts	38
Klik Rivet-Nuts/Ribbed.....	39
Metric Conversion Table.....	40

We will achieve business excellence by:

- ▶ Encouraging and expecting the creative involvement of every employee.
- ▶ Listening to our customers and meeting their needs.
- ▶ Continuously improving our processes, products and services.



Alcoa Fastening Systems (AFS) offers the broadest line of blind fasteners for industrial and automotive applications in the industry. The breadth of the line is supported by a nationwide network of independent stocking warehouses, maintaining inventories that can deliver product to customers within hours if necessary. In short, the company's responsiveness to its customers and the needs of industry is second to none.


In an ongoing effort to be the best, AFS offers custom services such as painting, plating, anodizing, packaging, bar-coding and labeling. Add to this a strong commitment to research, design and development and you have an unbeatable combination.

Quality Policy

Alcoa Fastening Systems is committed to satisfying our customers by delivering safe and reliable products; and achieving measurable objectives through continually improving process management.

General Information

Rivet Styles



Open End



Closed End



Multi-Grip



Tri-Bulb



Q-Lok



Klik-Lok



T-Rivets



Special Application
Rivets



Plastic

Features/Benefits

- For blind fastening where there is no access to opposite side of work
- Simple to install
- Wide variety of head styles and lengths available from $\frac{3}{32}$ " to $\frac{1}{4}$ " diameters

- Moisture-resistant due to tight seal
- Greater shear and tensile strength
- Mandrel is retained 100% of time
- $\frac{1}{8}$ " to $\frac{1}{4}$ " diameters

- Extended grip range capacity
- Reduces inventory (fewer sizes required)
- Use as a standard open end rivet
- $\frac{1}{8}$ " to $\frac{3}{16}$ " diameters

- Large footprint on blind side
- Multi-grip capability
- Oversized hole tolerant
- Great for soft or brittle materials

- Retained mandrel increases shear and tensile strength
- Use in high vibration applications
- Mandrel breaks flush when used in mid-grip range
- Moisture-resistant due to tight seal
- $\frac{1}{8}$ " to $\frac{3}{16}$ " diameters

- Permanently retained mandrel provides increased shear and tensile values
- Use in high vibration applications
- Provides weather-resistant joint
- Available in $\frac{3}{16}$ " and $\frac{1}{4}$ " diameters

- High clamp up
- High shear strength
- Creates a wide bearing surface
- $\frac{1}{4}$ " diameter

- Small flange rivet used primarily for fastening decorative materials on boats, automobiles, trucks & other motor vehicles
- Best suited to applications where a discreet, secure installation of non-critical components is needed.

- Precision-molded, all-nylon
- Secure lock prevents pull-out
- Fasten plastic to plastic, plastic to metal or plastic to fiberglass

Materials Available

Steel/steel, Aluminum/aluminum
Aluminum/steel, Stainless/stainless
Stainless/steel, Copper/brass, Copper/steel

Aluminum/steel, Aluminum/aluminum,
Stainless/stainless

Aluminum/steel, Steel/steel

Aluminum/aluminum

Steel/steel

Steel/steel, Aluminum/aluminum,
Stainless/stainless

Aluminum/steel

Stainless/steel, Aluminum/aluminum

General Information

Selecting the Correct Klik-Fast Rivet

Alcoa Fastening Systems offers a full line of headed Marson brand rivets for general consumer and industrial applications. The materials and manufacturing processes used to head rivet bodies increase their shear and tensile values over a stamped eyelet-style rivet. These easy-to-use rivets are used to fasten together two or more pieces of material of varying thickness.

The rivet body alloy, in addition to being chosen for strength requirements, should also be selected for compatibility with the materials to be joined to avoid galvanic corrosion caused by coupling dissimilar metals. If dissimilar metals are widely separated on the galvanic chart, it is advisable to separate them with a dielectric material such as paint or other coating.

Head Styles

Buttonhead



Large Flange



Countersunk



Features/Benefits

- Low profile head diameter is twice the rivet body diameter, providing adequate bearing surface for nearly all applications
- Open-end buttonhead rivets offer the broadest selection of sizes available.
- Provides greater bearing surface for fastening soft and brittle facing materials and oversize facing holes
- Works well with soft materials, where the increased flange diameter protects the integrity of the application
- 120° countersunk rivets for applications where flush appearance is required

Design Information

Rivet Code Definitions


Example:

ABL6-6A

- A — First LetterRivet material (A - Aluminum, S - Steel, C -Copper, SS - Stainless Steel)
B — Second LetterStyle of Head (B - Buttonhead, C - Countersunk)
L — Third Letter (if any)Large Flange Head
6 — First NumberBody Diameter in 32nd's
6 — Second NumberMaximum Grip Length in 16th's
A — Final Letter (S)..... A - Aluminum Mandrel, S - Stainless Steel Mandrel, B - Brass Mandrel,
C - Copper Plated Steel Mandrel, CLD - Closed-End, MG - Multi-Grip,
QL - Q-Lok, KL - Klik-Lok. No letter indicates steel mandrel.


Design Information

1. The shear and tensile strength of the rivet selected and the number of rivets used in the application should equal or exceed the joint strength requirements. Typical ultimate shear and tensile strengths are listed by diameter and alloy on pages 5 through 16 of this catalog. Testing is recommended before final selection and use in product.
2. The rivet body material should be compatible with the materials to be joined to resist galvanic corrosion which may result in reduction of joint strength. If dissimilar materials are widely separated on the galvanic chart, it is advisable to separate them with a dielectric material such as paint or other coating. AFS can paint colors to match, as well as anodize or plate to your specifications.
3. After determination of strengths required by diameter and alloy, the total thickness of materials to be joined must be considered. The grip range for each rivet is listed on pages 5 through 16. Select the rivet grip range which includes the total thickness of materials to be joined. Please note that the rivet barrel length (Column L) is not the grip range.
4. Recommended hole sizes listed for each rivet diameter on pages 5 through 16 should be followed closely. An undersize hole will not allow insertion of the rivet body; an oversize hole will reduce shear and tensile strengths, and may cause improper rivet setting, all of which promote joint failure.
5. The various head styles (illustrated page 3) are offered to accommodate different assembly needs. The most popular Klik-Fast rivet is the buttonhead, whose lower-profile head is twice the diameter of the rivet body. This provides adequate bearing surface for nearly all applications. The large flange Klik-Fast rivet provides greater bearing surface for fastening soft or brittle facing materials. The countersunk Klik-Fast rivet is available for applications where a flush appearance is required. And the closed-end is ideal for electric or electronics applications.
6. Besides the sizes, alloys and head styles listed, AFS manufactures a wide range of special rivets to accommodate a variety of customer needs for strength, head style and grip range. You are invited to send your applications questions or problems to Stoughton Operations for evaluation, testing and recommendations.
 - Samples are available upon request.
 - Special packaging needs are quickly and easily met.




Design Information


To install



Features, benefits & applications



Steel Rivets




Plated-Steel Rivet • Coated Steel Mandrel • IFI Grade 30

Buttonhead AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range Inch (mm)	Typical Ultimate Strength (Lbs.) (newtons) Shear Tensile	
							160 200	711 889
SB3-2	3/32"(.094)	#41(.097-.100)	.188	.032	.250	6.4	.032-.125	0.8-3.2
SB3-4	2.4	2.5(2.46-2.54)	4.78	0.81	.375	9.5	.126-.250	3.3-6.4
SB4-1	1/8"(.125)	#30(.129-.133)	.250	.040	.212	5.4	.032-.062	0.8-1.6
SB4-2	3.2	3.3(3.28-3.38)	6.35	1.02	.275	7.0	.063-.125	1.7-3.2
SB4-3					.337	8.6	.126-.187	3.3-4.8
SB4-4					.400	10.2	.188-.250	4.9-6.4
SB4-5					.462	11.7	.251-.312	6.5-7.9
SB4-6					.525	13.4	.313-.375	8.0-9.5
SB4-8					.650	16.5	.376-.500	9.6-12.7
SB4-10					.775	19.7	.501-.625	12.8-15.9
SB5-2	5/32"(.156)	#20(.160-.164)	.312	.050	.300	7.6	.062-.125	1.6-3.2
SB5-3	4.0	4.1(4.06-4.16)	7.92	1.27	.362	9.2	.126-.187	3.3-4.8
SB5-4					.425	10.8	.188-.250	4.9-6.4
SB5-6					.550	14.0	.251-.375	6.5-9.5
SB5-8					.675	17.2	.376-.500	9.6-12.7
SB5-10					.800	20.3	.501-.675	12.7-17.1
SB5-12					.925	23.5	.676-.750	17.2-19.1
SB6-2	3/16"(.187)	#11(.192-.196)	.375	.060	.325	8.3	.062-.125	1.6-3.2
SB6-4	4.8	4.9(4.88-4.98)	9.53	1.52	.450	11.5	.126-.250	3.3-6.4
SB6-6					.575	14.6	.251-.375	6.5-9.5
SB6-8					.700	17.8	.376-.500	9.6-12.7
SB6-10					.825	21.0	.501-.625	12.8-15.9
SB6-12					.950	24.2	.626-.750	16.0-19.1
SB6-14					1.075	27.3	.751-.875	19.1-22.2
SB6-16					1.200	30.5	.876-1.000	22.3-25.4
SB8-2	1/4"(.250)	F(.257-.261)	.500	.080	.370	9.4	.062-.125	1.6-3.2
SB8-4	6.4	6.5(6.53-6.63)	12.70	2.03	.500	12.7	.062-.250	1.6-6.4
SB8-6					.625	15.9	.251-.375	6.5-9.5
SB8-8					.750	19.1	.376-.500	9.6-12.7
SB8-10					.875	21.0	.501-.625	12.8-15.9
SB8-12					1.000	25.4	.626-.750	16.0-19.1
SB8-14					1.125	28.6	.751-.875	19.1-22.2
SB8-16					1.250	31.8	.876-1.000	22.3-25.4

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Steel Rivets



Plated-Steel Rivet • Coated Steel Mandrel • IFI Grade 30


Large Flange		D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range Inch (mm)	Typical Ultimate Strength (Lbs.) (newtons)	
AFS Part No.								Shear	Tensile
SBL4-2	1/8"(.125)	#30(.129-.133)	.375	.065	.275	7.0	.032-.125	0.8-3.2	305 410
SBL4-3	3.2	3.3(3.28-3.38)	9.53	1.65	.337	8.6	.126-.187	3.3-4.8	1356 1823
SBL4-4					.400	10.2	.188-.250	4.9-6.4	
SBL4-6					.525	13.3	.251-.375	6.5-9.5	
SBL4-8					.650	16.5	.376-.500	9.6-12.7	
SBL5-4	5/32"(.156)	#20(.160-.164)	.468	.070	.425	10.8	.188-.250	4.9-6.4	420 600
SBL5-6	4.0	4.1	11.90	1.77	.550	14.0	.251-.375	6.5-9.5	1868 2668
SBL5-8					.675	17.2	.376-.500	9.6-12.7	
SBL6-4	3/16"(.187)	#11(.192-.196)	.615	.090	.450	11.5	.062-.250	1.6-6.4	610 870
SBL6-6	4.8	4.9(4.88-4.98)	15.88	2.28	.575	14.6	.251-.375	6.5-9.5	2713 3869
SBL6-8					.700	17.8	.376-.500	9.6-12.7	
SBL6-10					.825	21.0	.501-.625	12.8-15.9	
SBL6-12					.950	24.2	.626-.750	16.0-19.1	
SBL6-14					1.075	27.3	.751-.875	19.2-22.2	
SBL6-16					1.200	30.5	.876-1.000	22.3-25.4	

120° Countersunk

SC4-2	1/8"(.125)	#30(.129-.133)	.220	.031 REF	.275	7.0	.062-.125	1.6-3.2	305 410
SC4-3	3.2	3.3(3.28-3.38)	5.59	1.14	.337	8.6	.126-.187	3.3-4.8	1356 1823
SC4-4					.400	10.2	.188-.250	4.9-6.4	
SC4-6					.525	13.3	.251-.375	6.5-9.5	
SC4-8					.650	16.5	.376-.500	9.6-12.7	
SC5-4	5/32"(.156)	#20(.160-.164)	.281	.040 REF	.425	10.8	.062-.250	1.6-6.4	420 600
	4.0	4.1	7.2	1.20					1868 2668
SC6-4	3/16"(.187)	#11(.192-.196)	.350	.050 REF	.450	11.4	.126-.250	3.3-6.4	610 870
SC6-6	4.8	4.9(4.88-4.98)	8.89	1.27	.575	14.6	.251-.375	6.5-9.5	2713 3869

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Aluminum Rivets




5052 Aluminum Rivet • Aluminum Mandrel • IFI Grade 11

Buttonhead AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range Inch (mm)	Typical Ultimate Strength (Lbs.) (newtons) Shear Tensile
AB3-2A	.332".(094)	#41(.097-.100)	.188	.032	.250 6.4	.032-.125 0.8-3.2	80 120
AB3-4A	2.4	2.5(2.46-2.54)	4.78	0.81	.375 9.5	.126-.250 3.3-6.4	355 533
AB4-1A	1/8"(.125)	#30(.129-.133)	.250	.040	.212 5.4	.032-.062 0.8-1.6	155 240
AB4-2A	3.2	3.3(3.28-3.38)	6.35	1.02	.275 7.0	.063-.125 1.7-3.2	689 1067
AB4-3A					.337 8.6	.126-.187 3.3-4.8	
AB4-4A					.400 10.2	.188-.250 4.9-6.4	
AB4-5A					.462 11.7	.251-.312 6.5-7.9	
AB4-6A					.525 13.4	.313-.375 8.0-9.5	
AB4-8A					.650 16.5	.376-.500 9.6-12.7	
AB4-10A					.775 19.7	.501-.625 12.8-15.9	
AB5-2A	5/32"(.156)	#20(.160-.164)	.312	.050	.300 7.6	.062-.125 1.6-3.2	230 340
AB5-3A	4.0	4.1(4.06-4.16)	7.92	1.27	.362 9.2	.126-.187 3.3-4.8	1023 1512
AB5-4A					.425 10.8	.188-.250 4.9-6.4	
AB5-6A					.550 14.0	.251-.375 6.5-9.5	
AB5-8A					.675 17.2	.376-.500 9.6-12.7	
AB5-10A					.800 20.3	.501-.625 12.7-17.1	
AB5-12A					.925 23.5	.626-.750 17.2-19.1	
AB6-2A	3/16"(.187)	#11(.192-.196)	.375	.060	.325 8.3	.062-.125 1.6-3.2	330 515
AB6-4A	4.8	4.9(4.88-4.98)	9.53	1.52	.450 11.5	.126-.250 3.3-6.4	1467 2290
AB6-6A					.575 14.6	.251-.375 6.5-9.5	
AB6-8A					.700 17.8	.376-.500 9.6-12.7	
AB6-10A					.825 21.0	.501-.625 12.8-15.9	
AB6-12A					.950 24.2	.626-.750 16.0-19.1	
AB6-14A					1.075 27.3	.751-.875 19.1-22.2	
AB6-16A					1.200 30.5	.751-1.00 19.2-25.4	
AB6-20A					1.450 36.8	1.125-1.250 28.6-31.8	
AB8-4A	1/4"(.250)	F(.257-.261)	.500	.080	.500 12.7	.062-.250 1.6-6.4	600 800
AB8-6A	6.4	6.5(6.53-6.63)	12.70	1.88	.625 15.9	.251-.375 6.5-9.5	2668 3558
AB8-8A					.750 19.1	.376-.500 9.6-12.7	
AB8-10A					.875 21.0	.501-.625 12.8-15.9	
AB8-12A					1.000 25.4	.626-.750 16.0-19.1	
AB8-14A					1.125 28.6	.751-.875 19.1-22.2	

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Aluminum Rivets



5052 Aluminum Rivet • Aluminum Mandrel • IFI Grade 11

Large Flange


AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range Inch (mm)	Typical Ultimate Strength (Lbs.) (newtons)	
							Shear	Tensile
ABL4-2A	1/8"(.125)	#30(.129-.133)	.375	.065	.275 7.0	.032-.125 0.8-3.2	155	240
ABL4-3A	3.2	3.3(3.28-3.38)	9.53	1.14	.337 8.6	.126-.187 3.3-4.8	689	1067
ABL4-4A					.400 10.2	.188-.250 4.9-6.4		
ABL4-6A					.525 13.3	.251-.375 6.5-9.5		
ABL4-8A					.650 16.5	.376-.500 9.6-12.7		
ABL5-4A	532"(.156) 4.0	#20(.160-.164) 4.1(4.06-4.16)	.468 11.9	.070 1.20	.425 10.8	.063-.250 1.6-6.4	230	340 1023 1512
ABL6-4A	3/16"(.187)	#11(.192-.196)	.615	.090	.450 11.5	.062-.250 1.6-6.4	330	515
ABL6-6A	4.8	4.9(4.88-4.98)	15.88	2.28	.575 14.6	.251-.375 6.5-9.5	1467	2290
ABL6-8A					.700 17.8	.376-.500 9.6-12.7		
ABL6-10A					.825 21.0	.501-.625 12.8-15.9		
ABL6-12A					.950 24.2	.626-.750 16.0-19.1		
ABL6-16A					1.200 30.5	.875-1.00 22.2-25.4		
ABL6-20A					1.450 36.8	1.125-1.250 28.6-31.8		

120° Countersunk

AC4-2A	1/8"(.125)	#30(.129-.133)	.220	.031 REF	.275 7.0	.062-.125 1.6-3.2	155	240
AC4-3A	3.2	3.3(3.28-3.38)	5.59	1.14	.337 8.6	.126-.187 3.3-4.8	689	1050
AC4-4A					.400 10.2	.188-.250 4.9-6.4		
AC4-6A					.525 13.3	.251-.375 6.5-9.5		
AC5-4A	532"(.156)	#20(.160-.164)	.281	.040 REF	.425 10.8	.188-.250 4.9-6.4	230	340
AC5-6A	4.0	4.1(4.06-4.16)	7.2	1.20	.550 14.0	.251-.375 6.5-9.5	1020	1512
AC6-4A	3/16"(.187)	#11(.192-.196)	.350	.050 REF	.407 10.3	.126-.250 3.3-6.4	330	515
AC6-6A	4.8	4.9(4.88-4.98)	8.89	1.27	.575 14.6	.251-.375 6.5-9.5	1467	2290
AC6-8A					.700 17.8	.376-.500 9.6-12.7		

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Aluminum/Steel Rivets




5056 Aluminum Rivet • Coated Steel Mandrel • IFI Grade 19

Buttonhead

AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range Inch (mm)	Typical Ultimate Strength (Lbs.) (newtons)	
							Shear	Tensile
AB3-2	.332".(094)	#41(.097-.100)	.188	.032	.250	6.4	.032-.125	0.8-3.2
AB3-4	2.4	2.5(2.46-2.54)	4.78	0.81	.375	9.5	.126-.250	3.3-6.4
AB4-1	1/8"(.125)	#30(.129-.133)	.250	.040	.212	5.4	.032-.062	0.8-1.6
AB4-2	3.2	3.3(3.28-3.38)	6.35	1.02	.275	7.0	.063-.125	1.7-3.2
AB4-3					.337	8.6	.126-.187	3.3-4.8
AB4-4					.400	10.2	.188-.250	4.9-6.4
AB4-5					.462	11.7	.251-.312	6.5-7.9
AB4-6					.525	13.4	.313-.375	8.0-9.5
AB4-8					.650	16.5	.376-.500	9.6-12.7
AB4-10					.775	19.7	.501-.625	12.8-15.9
AB5-2	5/32"(.156)	#20(.160-.164)	.312	.050	.300	7.6	.062-.125	1.6-3.2
AB5-3	4.0	4.1(4.06-4.16)	7.92	1.27	.362	9.2	.126-.187	3.3-4.8
AB5-4					.425	10.8	.188-.250	4.9-6.4
AB5-6					.550	14.0	.251-.375	6.5-9.5
AB5-8					.675	17.2	.376-.500	9.6-12.7
AB6-2	3/16"(.187)	#11(.192-.196)	.375	.060	.325	8.3	.062-.125	1.6-3.2
AB6-4	4.8	4.9(4.88-4.98)	9.53	1.52	.450	11.5	.126-.250	3.3-6.4
AB6-6					.575	14.6	.251-.375	6.5-9.5
AB6-8					.700	17.8	.376-.500	9.6-12.7
AB6-10					.825	21.0	.501-.625	12.8-15.9
AB6-12					.950	24.2	.626-.750	16.0-19.1
AB6-16					1.200	30.5	.751-1.00	19.2-25.4
AB8-4	1/4"(.250)	F(.257-.261)	.500	.080	.500	12.7	.062-.250	1.6-6.4
AB8-6	6.4	6.5(6.53-6.63)	12.70	1.88	.625	15.9	.251-.375	6.5-9.5
AB8-8					.750	19.1	.376-.500	9.6-12.7
AB8-10					.875	21.0	.501-.625	12.8-15.9
AB8-12					1.000	25.4	.626-.750	16.0-19.1
AB8-14					1.125	28.6	.751-.875	19.1-22.2
AB8-16					1.250	31.8	.876-1.000	22.3-25.4

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Aluminum/Steel Rivets



5056 Aluminum Rivet • Coated Steel Mandrel • IFI Grade 19

Large Flange


AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)		Grip Range Inch (mm)		Typical Ultimate Strength (Lbs.) (newtons)	
					Inch	mm	Inch	mm	Shear	Tensile
ABL4-2	1/8"(.125)	#30(.129-.133)	.375	.065	.275	7.0	.032-.125	0.8-3.2	225	315
ABL4-3	3.2	3.3(3.28-3.38)	9.53	1.65	.337	8.6	.126-.187	3.3-4.8	1000	1401
ABL4-4					.400	10.2	.188-.250	4.9-6.4		
ABL4-6					.525	13.3	.251-.375	6.5-9.5		
ABL5-4	5/32"(.156)	#20(.160-.164)	.468	.070	.425	10.8	.126-.250	3.2-6.4	300	470
	4.0	4.1(4.06-4.16)	11.9	1.78					1334	2090
ABL6-4	3/16"(.187)	#11(.192-.196)	.615	.090	.450	11.5	.062-.250	1.6-6.4	465	700
ABL6-6	4.8	4.9(4.88-4.98)	15.88	2.08	.575	14.6	.251-.375	6.5-9.5	2068	3113
ABL6-8					.700	17.8	.376-.500	9.6-12.7		
ABL6-10					.825	21.0	.501-.625	12.8-15.9		
ABL6-12					.950	24.2	.626-.750	16.0-19.1		
ABL6-14					1.075	27.3	.751-.875	19.1-22.2		
ABL6-16					1.200	30.5	.876-1.000	22.3-25.4		

120° Countersunk

AC4-2	1/8"(.125)	#30(.129-.133)	.220	.031 REF	.275	7.0	.062-.125	1.6-3.2	225	315
AC4-3	3.2	3.3 (3.28-3.38)	5.59	1.14	.337	8.6	.126-.187	3.3-4.8	1000	1401
AC4-4					.400	10.2	.188-.250	4.9-6.4		
AC4-5					.462	11.7	.251-.312	6.5-7.9		
AC5-4	5/32"(.156)	#20(.160-.164)	.281	.040 REF	.425	10.8	.188-.250	4.9-6.4	300	470
AC5-6	4.0	4.1(4.06-4.16)	7.2	1.20	.550	14.0	.251-.375	6.5-9.5	1334	2090
AC5-8					.675	17.2	.376-.500	9.6-12.7		
AC6-4	3/16"(.187)	#11(.192-.196)	.350	.050 REF	.407	10.3	.126-.250	3.3-6.4	465	700
AC6-6	4.8	4.9(4.88-4.98)	8.89	1.27	.575	14.6	.251-.375	6.5-9.5	2068	3113
AC6-8					.700	17.8	.376-.500	9.6-12.7		

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Stainless Rivets



Stainless Rivet • Stainless Mandrel • IFI Grade 51

Buttonhead AFS Part No.	D Rivet Dia. Nom. Inch (mm)	H Drill No. & Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range	Typical Ultimate Strength (Lbs. (newtons))		
					Inch (mm)	Inch (mm)	Shear	Tensile
SSB4-1S	1/8"(.125)	#30(.129-.133)	.250	.040	.212	5.4	.032-.062	0.8-1.6
SSB4-2S	3.2	3.3(3.28-3.38)	6.35	1.02	.275	7.0	.063-.125	1.7-3.2
SSB4-3S					.337	8.6	.126-.187	3.3-4.8
SSB4-4S					.400	10.2	.188-.250	4.9-6.4
SSB4-5S					.462	11.7	.251-.312	6.5-7.9
SSB4-6S					.525	13.4	.313-.375	8.0-9.5
SSB4-8S					.650	16.5	.376-.500	9.6-12.7
SSB5-2S	5/32"(.156)	#20(.160-.164)	.312	.045	.300	7.6	.062-.125	1.6-3.2
SSB5-3S	4.0	4.1(4.06-4.16)	7.92	1.14	.338	8.0	.126-.187	3.2-4.8
SSB5-4S					.425	10.8	.188-.250	4.9-6.4
SSB5-6S					.550	14.0	.251-.375	6.5-9.5
SSB5-8S					.675	17.2	.376-.500	9.6-12.7
SSB5-10S					.800	20.3	.501-.625	12.8-15.9
SSB6-2S	3/16"(.187)	#11(.192-.196)	.375	.066	.325	8.3	.062-.125	1.6-3.2
SSB6-4S	4.8	4.9(4.88-4.98)	9.53	1.40	.450	11.5	.126-.250	3.3-6.4
SSB6-6S					.575	14.6	.251-.375	6.5-9.5
SSB6-8S					.700	17.8	.376-.500	9.6-12.7
SSB6-10S					.825	21.0	.501-.625	12.8-15.9
SSB6-12S					.950	24.2	.626-.750	16.0-19.1
SSB6-16S					1.200	30.5	.751-1.000	19.1-25.4
SSB8-4S	1/4"(.250)	F(.257-.261)	.500	.074	.500	12.7	.062-.250	1.6-6.4
SSB8-6S	6.4	6.5(6.53-6.63)	12.70	1.88	.625	15.9	.251-.375	6.5-9.5
SSB8-8S					.750	19.1	.376-.500	9.6-12.7
SSB8-10S					.875	21.0	.501-.625	12.8-15.9
SSB8-12S					1.000	25.4	.626-.750	16.0-19.1

Large Flange

SSBL4-2S	1/8"(.125)	#30(.129-.133)	.375	.045	.275	7.0	.032-.125	0.8-3.2	520	600
SSBL4-3S	3.2	3.3(3.28-3.38)	9.53	1.14	.337	8.6	.126-.187	3.3-4.8	2310	2660
SSBL4-4S					.400	10.2	.188-.250	4.9-6.4		
SSBL6-4S	3/16"(.187)	#11(.192-.196)	.615	.082	.450	11.5	.062-.250	1.6-6.4	1150	1300
SSBL6-6S	4.8	4.9(4.88-4.98)	15.88	2.08	.575	14.6	.251-.375	6.5-9.5	5110	5780
SSBL6-8S					.700	17.8	.376-.500	9.6-12.7		
SSBL6-10S					.825	21.0	.501-.625	12.8-15.9		
SSBL6-12S					.950	24.2	.626-.750	16.0-19.1		

120° Countersunk

SSC4-2S	1/8"(.125)	#30(.129-.133)	.220	.045	.275	7.0	.063-.125	1.7-3.2	520	600
SSC4-3S	3.2	3.3(3.28-3.38)	5.59	1.14	.337	8.6	.126-.187	3.3-4.8	2310	2660
SSC4-4S					.400	10.2	.188-.250	4.9-6.4		
SSC4-5S					.462	11.7	.251-.312	6.5-7.9		
SSC6-4S	3/16"(.187)	#11(.192-.196)	.350	.050	.407	10.3	.126-.250	3.3-6.4	1150	1300
	4.8	4.9(4.88-4.98)	8.89	1.27					5110	5780

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Meet our
stainless
lineup



Standard




Countersink



Closed-End

Stainless/Steel Rivets



Stainless Rivet • Coated Steel Mandrel • IFI Grade 50

Buttonhead

AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range	Typical Ultimate Strength (Lbs. (newtons))			
	Inch	mm	Inch	mm	Inch	mm	Shear	Tensile		
SSB4-1	1/8"(.125)	#30(.129-.133)	.250	.040	.212	5.4	.032-.062	0.8-1.6	520	600
SSB4-2	3.2	3.3(3.28-3.38)	6.35	1.02	.275	7.0	.063-.125	1.7-3.2	2310	2660
SSB4-3					.337	8.6	.126-.187	3.3-4.8		
SSB4-4					.400	10.2	.188-.250	4.9-6.4		
SSB4-5					.462	11.7	.251-.312	6.5-7.9		
SSB4-6					.525	13.4	.313-.375	8.0-9.5		
SSB4-8					.650	16.5	.376-.500	9.6-12.7		
SSB5-2	532"(.156)	#20(.160-.164)	.312	.045	.300	7.6	.062-.125	1.6-3.2	785	1040
SSB5-4	4.0	4.1(4.06-4.16)	7.92	1.14	.425	10.8	.126-.250	4.9-6.4	3490	4620
SSB5-6					.550	14.0	.251-.375	6.5-9.5		
SSB6-2	316"(.187)	#11(.192-.196)	.375	.055	.325	8.3	.062-.125	1.6-3.2	1150	1300
SSB6-4	4.8	4.9(4.88-4.98)	9.53	1.40	.450	11.5	.126-.250	3.3-6.4	5110	5780
SSB6-6					.575	14.6	.251-.375	6.5-9.5		
SSB6-8					.700	17.8	.376-.500	9.6-12.7		
SSB6-10					.825	21.0	.501-.625	12.8-15.9		
SSB6-12					.950	24.2	.626-.750	16.0-19.1		
SSB6-16					1.120	30.5	.751-1.000	19.2-25.4		

Large Flange

SSBL4-2	1/8"(.125)	#30(.129-.133)	.375	.045	.275	7.0	.032-.125	0.8-3.2	520	600
SSBL4-3	3.2	3.3(3.28-3.38)	9.53	1.14	.337	8.6	.126-.187	3.3-4.8	2310	2660
SSBL4-4					.400	10.2	.188-.250	4.9-6.4		
SSBL6-4	316"(.187)	#11(.192-.196)	.625	.082	.450	11.5	.062-.250	1.6-6.4	1150	1300
SSBL6-6	4.8	4.9(4.88-4.98)	15.88	2.08	.575	14.6	.251-.375	6.5-9.5	5110	5780
SSBL6-8					.700	17.8	.376-.500	9.6-12.7		
SSBL6-10					.825	21.0	.501-.625	12.8-15.9		
SSBL6-12					.950	24.2	.626-.750	16.0-19.1		

120° Countersunk

SSC4-2	1/8"(.125)	#30(.129-.133)	.220	.045	.275	7.0	.063-.125	1.7-3.2	520	600
SSC4-3	3.2	3.3(3.28-3.38)	5.59	1.14	.337	8.6	.126-.187	3.3-4.8	2310	2660
SSC4-4					.400	10.2	.188-.250	4.9-6.4		
SSC4-5					.462	11.7	.251-.312	6.5-7.9		
SSC6-4	316"(.187)	#11(.192-.196)	.350	.050	.407	10.3	.126-.250	3.3-6.4	1150	1300
	4.8	4.9(4.88-4.98)	8.89	1.27					5110	5780

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.


KLIK-FAST® stainless steel rivets from Alcoa Fastening Systems provide outstanding value and offer your assemblies:

- Corrosion resistance
- Multiple head styles
- High strength
- Widest size range $\frac{1}{8}'' - \frac{1}{4}''$



Whether the application is marine, medical or electronics, for long life of the assembly, count on Alcoa Fastening Systems. All Marson brand rivets conform to IFI specifications. Call today for more information on our entire line of high quality rivets and fastening tools.

Closed-End Rivets



5056 Aluminum/Steel Buttonhead • IFI Grade 19

AFS Part No.	D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max. Inch (mm)	Grip Range		Typical Ultimate Strength (Lbs. (newtons))	
						Inch	(mm)	Shear	Tensile
AB4-1CLD	1/8"(.126)	#30	.236	.050	.296	7.52	.032-.062	0.8-1.6	240 280
AB4-2CLD	3.2	(.129-.133)			.355	9.02	.063-.125	1.7-3.2	1060 1240
AB4-3CLD					.414	10.52	.126-.187	3.3-4.8	
AB4-4CLD					.437	11.10	.188-.250	4.9-6.4	
AB4-5CLD					.532	13.51	.251-.312	6.5-7.9	
AB4-6CLD					.591	15.06	.313-.375	8.0-9.5	
AB5-2CLD	5/32"(.157)	#20	.315	.065	.355	9.02	.063-.125	1.7-3.2	350 480
AB5-3CLD	4.0	(.160-.164)			.414	10.52	.126-.187	3.3-4.8	1550 2130
AB5-5CLD					.532	13.51	.188-.312	4.9-7.9	
AB6-2CLD	3/16"(.188)	#11	.374	.080	.355	9.02	.063-.125	1.7-3.2	500 690
AB6-4CLD	4.8	(.192-.196)			.437	11.10	.126-.250	3.3-6.4	2230 3070
AB6-6CLD					.591	15.06	.251-.375	6.5-9.5	
AB6-8CLD					.748	19.00	.376-.500	9.6-12.7	
AB6-10CLD					.866	22.00	.501-.625	12.8-15.9	
AB8-4CLD	1/4"(.252)	F	.512	.090	.532	13.51	.062-.250	1.6-6.4	900 1100
AB8-6CLD	6.4	(.257-.261)			.670	17.02	.251-.375	6.5-9.5	3950 5000

120° Countersunk

AC4-2CLD	1/8"(.126)	#30	.236	.050	.355	9.02	.063-.125	1.7-3.2	240 280
AC4-3CLD	3.2	(.129-.133)			.414	10.52	.126-.187	3.3-4.8	1060 1240
AC4-4CLD					.437	11.10	.188-.250	4.9-6.4	
AC6-4CLD	3/16"(.188)	#11	.374	.065	.437	11.10	.126-.250	3.3-6.4	500 690
	4.8	(.192-.196)							2230 3070

All Aluminum • IFI Grade 15

AB4-2ACLD	1/8"(.126)	#30	.236	.050	.355	9.02	.063-.125	1.7-3.2	99 108
AB4-3ACLD	3.2	(.129-.133)			.414	10.52	.126-.187	3.3-4.8	450 490
AB4-4ACLD					.437	11.10	.188-.250	4.9-6.4	
AB5-4ACLD	5/32"(.157)	#20	.315	.065	.437	11.10	.126-.250	3.3-6.4	127 180
	4.0	(.160-.164)							580 820
AB6-2ACLD	3/16"(.188)	#11	.374	.080	.355	9.02	.063-.125	1.7-3.2	198 246
AB6-4ACLD	4.8	(.192-.196)			.437	11.10	.126-.250	3.3-6.4	900 1120
AB6-6ACLD					.591	15.06	.251-.375	6.5-9.5	
AB6-8ACLD					.748	19.00	.376-.500	9.6-12.7	
AB6-10ACLD					.866	22.00	.501-.625	12.8-15.9	


All Stainless

SSB4-2SCLD	1/8"(.126)	#30	.236	.039	.355	9.02	.063-.125	1.7-3.2	441 551
SSB4-3SCLD	3.2	(.129-.133)	5.99	.990	.414	10.52	.126-.187	3.3-4.8	2000 2500
SSB4-4SCLD					.437	11.10	.188-.250	4.9-6.4	
SSB6-2SCLD	3/16"(.188)	#11	.374	.070	.355	9.02	.063-.125	1.7-3.2	991 1210
SSB6-4SCLD	4.8	(.192-.196)	9.49	1.77	.437	11.10	.126-.250	3.3-6.4	4500 5500
SSB6-6SCLD					.591	15.06	.251-.375	6.5-9.5	

Note: A slightly smaller mandrel diameter is required for closed-end rivets; therefore when setting closed-end rivets using Marson brand rivet setting tools, we recommend you use one size smaller nosepiece when possible (i.e., to set 1/8" rivets, use 3/32" nosepiece).

KLIK-FAST RIVETS conform to IFI-126 (inch). Millimeters (mm) and newtons (N) are in green.

Multi-Grip Rivets



Plated Steel Rivet • Plated Steel Mandrel* • IFI Grade 30

Steel Buttonhead

AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range Inch (mm)	Typical Ultimate Strength (Lbs.) (newtons) Shear Tensile
SB41-42MG	1/8"(.125)	#30(.129-.133)	.283	.033	.355 9.0	.043-.156 1.1-4.0	340 385
	3.2	3.3(3.28-3.38)	7.2	0.85			1510 1710
SB52-53MG	5/32"(.156)	#20(.160-.164)	.319	.047	.433 11.0	.056-.196 1.4-5.0	440 530
	4.0	4.1(4.06-4.16)	8.1	1.20			1960 2360
SB62-63MG	3/16"(.187)	#11(.192-.196)	.386	.069	.405 10.3	.047-.187 1.2-4.8	810 750
	4.8	4.9(4.88-4.98)	9.8	1.75			3605 3335
SB63-64MG					.500 12.7	.156-.250 4.0-6.3	1025 780
							4560 3470

Aluminum/Steel Buttonhead[†]

AB41-43MG	1/8"(.125)	#30(.129-.133)	.250	.037	.315 8.0	.031-.187 0.8-4.8	165 230
AB42-44MG	3.2	3.3(3.28-3.38)	6.35	0.95	.375 9.5	.046-.250 1.2-6.4	735 1025
AB44-45MG					.438 11.1	.156-.312 4.0-7.9	
AB45-46MG					.500 12.7	.216-.375 5.5-9.5	
AB52-54MG	5/32"(.156)	#20(.160-.164)	.312	.047	.375 9.5	.046-.250 1.2-6.4	255 375
AB54-56MG	4.0	4.1(4.06-4.16)	7.92	1.20	.500 12.7	.156-.375 4.0-9.5	1135 1670
AB56-58MG					.666 16.9	.250-.500 6.4-12.7	
AB62-64MG	3/16"(.187)	#11(.192-.196)	.386	.057	.406 10.3	.062-.250 1.6-6.4	350 530
AB63-67MG	4.8	4.9(4.88-4.98)	9.8	1.45	.595 15.1	.187-.437 4.8-11.1	1560 2360
AB66-68MG					.666 16.9	.250-.500 6.4-12.7	
AB610-612MG					.978 24.8	.500-.781 12.7-19.8	

Aluminum/Steel Large Flange


ABL42-43MG	1/8"(.125)	#30(.129-.133)	.325	.039	.315 8.0	.031-.187 0.8-4.8	165 230
ABL42-44MG	3.2	3.3(3.28-3.38)	8.25	1.00	.375 9.5	.046-.250 1.2-6.4	735 1025
ABL44-45MG					.438 11.1	.156-.312 4.0-7.9	
ABL52-54MG	5/32"(.156)	#20(.160-.164)	.374	.051	.375 9.5	.062-.250 1.6-6.4	255 375
ABL53-55MG	4.0	4.1(4.06-4.16)	9.5	1.30	.438 11.1	.125-.312 3.2-7.9	1135 1670
ABL55-58MG					.690 17.5	.251-.500 6.4-12.7	
ABL62-64MG	3/16"(.187)	#11(.192-.196)	.625	.069	.406 10.3	.062-.250 1.6-6.4	350 530
ABL66-68MG	4.8	4.9(4.88-4.98)	15.85	1.75	.666 16.9	.250-.500 6.4-12.7	1560 2360
ABL610-612MG					.978 24.8	.500-.781 12.7-19.8	

Aluminum/Steel 120° Countersunk

AC43-44MG	1/8"(.125)	#30(.129-.133)	.209	.029	.383‡ 9.7	.093-.250 2.4-6.4	155 206
	3.2	3.3(3.28-3.38)	5.3	0.75			690 912
AC53-55MG	5/32"(.156)	#20(.160-.164)	.252	.049	.470‡ 11.9	.109-.312 2.7-7.9	255 300
	4.0	4.1(4.06-4.16)	6.40	1.24			1135 1670
AC62-65MG	3/16"(.187)	#11(.192-.196)	.345	.051	.500‡ 12.7	.062-.312 1.6-7.9	350 530
AC66-68MG	4.8	4.9(4.88-4.98)	8.75	1.30	.690‡ 17.5	.250-.500 6.4-12.7	1560 2360

* Mandrel-Clear Passivate ‡ Mandrel-Zinc with Yellow Dichromate Finish † C.S.K.-Total Length (L) including head

Millimeters (mm) and newtons (N) are in green.




Multi-grip rivets provide an effective and economical alternative to other, more costly methods of fastening, because one size handles the grip range capacity of up to 3 standard open end rivets. Multi-grip rivets can be used in any application requiring open end rivets, while reducing inventory requirements. Use multi-grip rivets as a standard open-end rivet...no special tool is needed.

Copper Brass and Copper Steel Rivets




#110 Copper Rivet Brass or Copper Plated Steel Mandrel IFI Grade 20

AFS Part No.	D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max. Inch	Grip Range Inch	Typical Ultimate Strength (Lbs.) (newtons)
						Inch	Shear Tensile
CB4-2B; CB4-2C	1/8"(.125)	#30(.129-.133)	.125	.040	.275 7.0	.063-.125 1.7-3.2	215 300
CB4-4B; CB4-4C	3.2	3.3(3.28-3.38)	6.35	1.02	.400 10.2	.188-.250 4.9-6.4	950 1330

2B - Copper Brass; 2C - Copper Steel



Typical Ultimate Strength (Lbs.) (newtons)
Shear Tensile



Tri-Bulb Rivets

Plain Rivet	Black Rivet	D	A	E	H	M	Grip Range	N	Y	Shear		Tensile	
										Ibs.	newtons	Ibs.	newtons
A0516ATB	A0516ATB-GBK-1	0.157	0.091	0.055	0.315	1.890	.039 -.118	0.630	0.236	134	600	224	1000
A0523ATB	A0523ATB-GBK-1	0.157	0.091	0.055	0.315	2.087	.039 -.276	0.835	0.335	134	600	224	1000
A0619ATB	A0619ATB-GBK-1	0.188	0.115	0.071	0.386	2.008	.039 -.157	0.720	0.276	202	900	269	1200
A0622ATB	A0622ATB-GBK-1	0.188	0.115	0.071	0.386	2.205	.039 -.248	0.807	0.335	202	900	269	1200
A0625ATB	A0625ATB-GBK-1	0.188	0.115	0.071	0.386	2.205	.039 -.354	0.925	0.374	202	900	269	1200
A0630ATB	A0630ATB-GBK-1	0.188	0.115	0.071	0.386	2.362	.157 -.472	1.063	0.433	202	900	269	1200
AL0625ATB	AL0625ATB-GBK-1	0.188	0.115	0.079	0.551	2.205	.039 -.354	0.925	0.374	202	900	269	1200

White available as special order item.

Painted Rivets*

AFS Part No.	Rivet Color	D Rivet Dia. Norm. Inch	Drill No.& Hole Size	W=White		BR=Brown		BL=Black		Grip Range		Typical Ultimate Strength (lbs.) (newtons)	
				H Head Dia. Norm. Inch	E Head Height Max. Inch	L Rivet Length Max. Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Tensile		Shear	Tensile
AB4-2AW	W	1/8" (.125)	#30 (.129-.133)	.125	.040	.275	7.0	.062-.125	1.7-3.2	155	240		
AB4-3AW	W	3.2	3.3(3.28-3.38)	6.35	1.02	.337	8.6	.126-.187	3.2-4.8	689	1067		
AB4-4AW	W					.400	10.2	.188-.250	4.9-6.4				
AB4-2ABR	BR	1/8" (.125)	#30 (.129-.133)	.125	.040	.275	7.0	.062-.125	1.7-3.2	155	240		
AB4-3ABR	BR	3.2	3.3(3.28-3.38)	6.35	1.02	.337	8.6	.126-.187	3.2-4.8	689	1067		
AB4-4ABR	BR					.400	10.2	.188-.250	4.9-6.4				
AB4-2ABL	BL	1/8" (.125)	#30 (.129-.133)	.125	.040	.275	7.0	.062-.125	1.7-3.2	155	240		
AB4-3ABL	BL	3.2	3.3(3.28-3.38)	6.35	1.02	.337	8.6	.126-.187	3.2-4.8	689	1067		
AB4-4ABL	BL					.400	10.2	.188-.250	4.9-6.4				
SB4-2W	W	1/8" (.125)	#30 (.129-.133)	.125	.040	.275	7.0	.062-.125	1.7-3.2	305	410		
SB4-3W	W	3.2	3.3(3.28-3.38)	6.35	1.02	.337	8.6	.126-.187	3.2-4.8	1356	1823		
SB4-4W	W					.400	10.2	.188-.250	4.9-6.4				
SB4-2BR	BR	1/8" (.125)	#30 (.129-.133)	.125	.040	.275	7.0	.062-.125	1.7-3.2	305	410		
SB4-3BR	BR	3.2	3.3(3.28-3.38)	6.35	1.02	.337	8.6	.126-.187	3.2-4.8	1356	1823		
SB4-4BR	BR					.400	10.2	.188-.250	4.9-6.4				
SB4-2BL	BL	1/8" (.125)	#30 (.129-.133)	.125	.040	.275	7.0	.062-.125	1.7-3.2	330	515		
SB4-4BL	BL	3.2	3.3(3.28-3.38)	6.35	1.02	.400	10.2	.188-.250	4.9-6.4	1467	2290		
AB6-4AW	W	3/16" (.187)	#11(.192-.196)	.375	.060	.450	11.5	.126-.250	3.2-6.4	330	515		
AB6-4ABL	BL	4.8	4.9(4.88-4.98)	9.53	1.52	.450	11.5	.126-.250	3.2-6.4	1467	2290		

* Custom colors available; contact factory for additional information.

Back-Up Washers

AFS Part No.	Bulk Part No.	500 Pack No.	Standard Carton Qty.	Material	For Hole Size	Size/Shape
SS-3	50653	40653	5M	STEEL	3/32"	1/2" SQ
SS-4	50654	40654	5M	STEEL	1/8"	1/2" SQ
SS-6	50656	40656	5M	STEEL	3/16"	1/2" SQ
SS-8	50658	40658	10M	STEEL	1/8"	3/8" RD
SS-9	50655	40655	10M	STEEL	5/32"	7/16" RD
SS-10	50661	40661	10M	STEEL	3/16"	1/2" RD
SS-12	50662	40662	10M	STEEL	1/4"	1/2" RD
AS-8	50657	40657	10M	ALUMINUM	1/8"	3/8" RD
AS-9	50659	40659	10M	ALUMINUM	5/32"	7/16" RD
AS-10	50660	40660	10M	ALUMINUM	3/16"	1/2" RD
AS-12	50665	40665	10M	ALUMINUM	1/4"	1/2" RD

Back-up washers are .056"-.062" thick. They are used when fastening soft materials or to compensate for oversize holes where access to both sides of the work is possible.



Double-Ended Drill Bit/39100

This double-ended drill bit provides the correct size hole and angle for 1/8" diameter countersink rivets, drilling and countersinking in one operation.






**Plated Steel Body
Plated Steel Mandrel**

AFS Part No.	D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max. Inch (mm)	Grip Range Inch (mm)	Typical Ultimate Strength (Lbs.) (newtons)	
	Shear	Tensile						
SB4-2QL	1/8"(.125)	#30(.129-.133)	.250	.045	.300 7.6	.062-.125	1.6-3.2	500 400
SB4-4QL	3.2	3.3(3.28-3.38)	6.40	1.20	.425 10.8	.126-.250	3.3-6.4	2220 1780
SB5-2QL	5/32"(.156)	#20(.160-.164)	.312	.055	.325 8.3	.062-.125	1.6-3.2	700 550
SB5-4QL	4.0	4.1(4.06-4.16)	7.9	1.40	.450 11.4	.126-.250	3.3-6.4	3110 2440
SB6-2QL	3/16"(.187)	#11(.192-.196)	.375	.065	.350 8.9	.062-.125	1.6-3.2	1050 825
SB6-4QL	4.8	4.9(4.88-4.98)	9.5	1.65	.475 12.0	.126-.250	3.3-6.4	4670 3670
SB6-6QL					.600 15.2	.251-.375	6.5-9.5	
SB6-8QL					.725 18.4	.376-.500	9.6-12.7	

Aluminum/Steel†



Steel Q-Lok™ Rivets

52372	1/4"(.250)	F(.257-.261)	.500	.120	.520 13.22	.062-.125	1.58-3.18	1500	1000
52371	6.4	6.5(6.53-6.63)	12.7	3.00	.520 13.22	.032-.140	0.81-3.56	6670	4445
52368					.707 17.79	.251-.312	6.38-7.93		
52369					.770 19.56	.312-.375	7.95-9.53		
52370					.832 21.13	.376-.437	9.55-11.10		
50376					.960 24.38	.520-.620	13.21-15.97		

† Requires nosepiece No. 96028 when using the Marson brand Big Daddy® (39031) hand tool.

KLIK-FAST RIVETS conform to IFI-130 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

Automotive/Special Application Rivets

Trim Rivets

AFS Part No.	Description	Grip Range	Materials Body/Mandrel	Rivet Dia. Nom.	Flange Dia. Nom.	Hole Dia. Range	500 Pack No.	Applications
50261*	Trim Moulding Rivet	.126-.187	Alum/Alum	.125	.208	.129-.133	40261	(ABN4-3A)
50262*	Long Trim Moulding Rivet	.188-.250	Alum/Alum	.125	.208	.129-.133	40262	(ABN4-4A)
50516*	Trim Moulding Rivet w/SS Body	.126-.187	SS/Steel	.125	.208	.129-.133	40516	(SSBN4-3)

*Use 39112 Trim Clip Rivet Nosepieces with HP-2 or Kliker Riveter to form trim clip studs with 50261; 50262; 50516 rivets.

Klik-Split® Window & Door Rivets[†]

52371	Window Regulator Rivet	.032-.140	Alum/Steel	.250	.500	.257-.261	NA	GM 9436175
								Ford 385189
								Chry 6031115
52372	Outside Door Handle Rivet with recessed head	.090-.115	Alum/Steel	.250	.500	.257-.261	NA	Ford 388047-S100
52373	Door Handle Rivet w/recessed head and zinc coated mandrel	.110-.177	Alum/Steel	.250	.500	.257-.261	NA	GM 20713843
52374	Window Regulator Rivet w/yellow zinc coated mandrel	.140-.187	Alum/Steel	.250	.500	.257-.261	NA	GM 9437486
								Chry 6032926
52375	Blk. Anodized Door Handle Rivet	.090-.115	Alum/Steel	.250	.500	.257-.261	NA	Ford 388047-S102
50376	Glass Stop Rivet	.520-.620	Alum/Steel	.250	.500	.257-.261	NA	Ford 385323
								Chry 6031091

† Requires nosepiece No. 96028 when using the Marson brand Big Daddy® (39031) hand tool.

Bumper Rivets

53150	Bumper Fascia Rivet large flange black	.250-.375	Steel/Steel	.187	.625	.192-.196	NA	GM 9439719
53181	Bumper Fascia Rivet w/yellow zinc coated mandrel	.125-.250	Steel/Steel	.250	.500	.257-.261	NA	Ford 372820-S36

Miscellaneous Rivets

53295	Rear Window Gasket Rivet	.125-.187	Alum/Steel	.125	.325	.129-.130	NA	GM 20325696
53314	Multi-Purpose Rivet, large flange	.125-.187	Alum/Steel	.125	.375	.129-.130	NA	GM 9432552
53353	Trunk Lock Swivel Emblem Rivet sealed end, countersunk head	.126-.187	Alum/Steel	.156	.312	.160-.164	NA	GM 9432137
	Requires Nosepiece #39144							Chry 6032138

Klik-Lok™ Rivets

AFS Part No.	A Rivet Dia. Inch (mm)	Required Hole Size Inch (mm)	B Head Dia. Inch (mm)	C Head Height Max. Inch (mm)	D Body Length Max. Inch (mm)	E Overall Length Max. (mm)	F Length Max. Inch (mm)	Grip Range Inch (mm)	Average Shear Strength lbs. (newtons)	Average Tensile Strength lbs. (newtons)
	Steel Rivet • Steel Mandrel • Buttonhead									
SB6-4KL	.188 4.8	.191-.201 4.9-5.10	.385 9.77	.085 2.15	.415 10.45	.675 15.87	1.00 25.40	.062-.270 1.57-6.85	1450 6499	1200 5379
SB6-7KL					.572	.825	1.00	.214-.437		
SB6-EKL					14.52	20.95	25.40	5.43-11.09		
					.572	.950	1.00	.062-.437		
					14.52	24.13	25.40	1.57-11.09		
SB8-6KL	.257 6.5	.261-.272 6.6-6.9	.525 13.33	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	.080-.375 2.03-9.52	2750 12326	2200 9861
SB8-10KL					.810	1.220	1.00	.350-.625		
					20.57	30.98	25.40	8.89-15.75		
SB8-EKL					.810	1.405	1.00	.080-.625		
					20.57	35.68	25.40	2.03-15.87		
Large Flange										
SBL6-4KL	.188 4.8	.191-.201 4.9-5.1	.500 12.70	.085 2.15	.415 10.45	.675 15.87	1.00 25.40	.062-.270 1.57-6.85	1450 6499	1200 5379
SBL6-EKL					.572	950	1.00	.062-.437		
					14.52	24.13	25.40	1.57-11.09		
SBL8-6KL	.257 6.5	.261-.272 6.6-6.9	.588 14.93	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	.080-.375 2.03-9.52	2750 12326	2200 9861
100° Countersunk										
SC6-6KL	.188 4.8	.191-.201 4.9-5.1	.345 8.8	.070 1.8	.486 12.34	.762 19.35	1.00 25.40	.125-.331 3.17-8.40	1450 6499	1200 5379
SC6-9KL					.653	.929	1.00	.305-.500		
					16.58	23.59	25.40	7.74-12.70		
SC8-8KL	.257 6.5	.261-.272 6.6-6.9	.405 10.3	.079 2.0	.660 16.76	1.059 26.89	1.00 25.40	.160-.475 4.06-12.06	2750 12326	2200 9861
SC8-12KL					.910	1.309	1.00	.415-.725		
					23.11	33.24	25.40	10.54-18.41		


Note: All orange shaded items are special order only; minimums apply.

Klik-Lok™ Rivets

AFS Part No.	A Rivet Dia. Inch (mm)	Required Hole Size Inch (mm)	B Head Dia. Inch (mm)	C Head Height Max. Inch (mm)	D Body Length Max. Inch (mm)	E Overall Length Max. (mm)	F Length Max. Inch (mm)	Grip Range Inch (mm)	Average Shear Strength lbs. (newtons)	Average Tensile Strength lbs. (newtons)
	AB6-4AKL	.188 4.8	.191-.201 4.9-5.1	.385 9.8	.085 2.15	.415 10.54	.675 15.87	1.00 25.40	.062-.270 1.57-6.85	700 3138
Aluminum Rivet • Aluminum Mandrel • Buttonhead										
AB6-7AKL					.572	.825	1.00	.214-.437		
					14.52	20.95	25.40	5.43-11.09		
AB6-AEKL					.572	950	1.00	.062-.437		
					14.52	24.13	25.40	1.57-11.09		
AB8-6AKL	.257 6.5	.261-.272 6.6-6.9	.525 13.33	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	.080-.375 2.03-9.52	1300 5827	890 3989
AB8-10AKL					.810	1.220	1.00	.350-.625		
					20.57	30.98	25.40	8.89-15.87		
AB8-AEKL					.810	1.405	1.00	.080-.625		
					20.57	35.56	25.40	2.03-15.87		
Large Flange										
ABL6-4AKL	.188 4.8	.191-.201 4.9-5.1	.500 12.7	.085 2.15	.415 10.45	.675 15.87	1.00 25.40	.062-.270 1.57-6.85	700 3138	500 2241
ABL6-7AKL					.572	.825	1.00	.214-.437		
					14.52	20.95	25.40	5.43-11.09		
100° Countersunk										
AC6-6AKL	.188 4.8	.191-.201 4.9-5.1	.345 8.8	.070 1.8	.486 12.34	.762 19.35	1.00 25.40	.125-.331 3.17-8.40	700 3138	500 2241
AC6-9AKL					.653	.929	1.00	.305-.500		
					16.58	23.59	25.40	7.74-12.70		
AC8-8AKL	.257 6.5	.261-.272 6.6-6.9	.405 10.3	.079 2.0	.660 16.76	1.059 26.89	1.00 25.40	.160-.475 4.06-12.06	1300 5827	890 3989
AC8-12AKL					.910	1.309	1.00	.415-.725		
					23.11	33.24	25.40	10.54-18.41		

Note: All orange shaded items are special order only; minimums apply.

Klik-Lok™ Rivets



AFS Part No.	Rivet Dia. Inch (mm)	Required Hole Size Inch (mm)	Head Dia. Inch (mm)	Head Height Max. Inch (mm)	Body Length Max. Inch (mm)	Overall Length Max. (mm)	F Length Max. Inch (mm)	Grip Range Inch (mm)	Average Shear Strength lbs. (newtons)	Average Tensile Strength lbs. (newtons)
-----------------	----------------------------	---------------------------------------	---------------------------	----------------------------------	----------------------------------	--------------------------------	----------------------------------	----------------------------	--	--

Stainless Rivet • Stainless Mandrel • Buttonhead


SSB6-4SKL	.188 4.8	.191-.201 4.9-5.1	.385 9.8	.085 2.15	.415 10.54	.625 17.14	1.00 25.40	.062-.270 1.57-6.85	1400 6275	1000 4482
SSB6-7SKL					.572	.825	1.00	.214-.437		
					14.52	20.95	25.40	5.43-11.09		
SSB6-ESKL					.572	.950	1.00	.062-.437		
					14.52	24.13	25.40	1.57-11.09		
SSB8-6SKL	.257 6.5	.261-.272 6.6-6.9	.525 13.3	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	.080-.375 2.03-9.52	2500 11206	2000 8964
SSB8-10SKL					.810	1.220	1.00	.350-.625		
					20.57	30.98	25.40	8.89-15.87		

100° Countersunk

SSC6-6SKL	.188 4.8	.191-.201 4.9-5.1	.345 8.8	.070 1.8	.486 12.34	.762 19.35	1.00 25.40	.125-.331 3.17-8.40	1400 6275	1000 4482
SSC8-8SKL	.257 6.5	.261-.272 6.6-6.9	.405 10.3	.079 2.0	.560 14.62	1.059 26.89	1.00 25.40	.160-.475 4.06-12.06	2500 11206	2000 8964

Millimeters (mm) and newtons (n) are in green.

Klik-Lok™ Rivets



1 After drilling hole to proper diameter, rivet is placed into hole and rivet setting tool is placed over mandrel.

2 Actuating tool starts mandrel into rivet body, pulling work material together and expanding body on the blind side.

3 A solid circle lock is created between the body and mandrel creating a weather resistant assembly that virtually eliminates pin pushout.

4 After the mandrel is broken, the mandrel is flush with the rivet body removing the need for grinding.

5 The expansion of the body tightly fills the hole creating a weather-resistant joint, and the flush break eliminates the need for grinding.

Material and Finish

Material	Sleeve	Pin	Sleeve Finish	Pin Finish
Steel	Low Carbon Steel	Medium Carbon Steel	Zinc Plated Clear Chromate	Zinc Plated Gold Chromate
Aluminum	5056	7075	Clear Chromate	Gold Chromate
Stainless	302	305/304	Passivated	Dry Lubricated

Pin Retention Values (lbs.)


	Steel	Aluminum	Stainless Steel
3/16"	Pin Retention	300	50
1/4"	Pin Retention	500	100



Equivalent to Monobolt®, TigerBolt®, Magna Lok®, Ultra-Grip® and Mega-Grip®.

When setting Marson brand Klik-Lok rivets, **no special nosepiece** is required.

Plastic Rivets



Plastic rivet before and after

Klik-Lok Plastic Rivets


Marson brand Klik-Lok Plastic Rivets are the same precision-molded all-nylon rivets used by domestic auto manufacturers, both for original equipment and replacement parts. In addition, Klik-Lok Plastic Rivets are ideal for non-conductive and non-corrosive environments. Klik-Lok Plastic Rivets fasten plastic to plastic, plastic to metal and plastic to fiberglass. As they set, three "legs" form to securely lock the components in place and prevent pullout.

Diagram Reference	100-Pack Part No.*	D Rivet Dia. Nom. Inch	H Hole Size Inch (mm)	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max. Inch	Grip Range Inch	Typical Ultimate Strength (Lbs.)	
								Shear	Tensile
A	48286	.154	.156 (4)	.315	.098	1.024	.236 - .413	40	82
B	48305	.195	.197 (5)	.472	.130	.728	.059 - .177	68	120
C	48306	.195	.197 (5)	.472	.071	.787	.118 - .236	68	120
D	48307	.195	.197 (5)	.472	.071	.787	.118 - .177	68	120
E	48308	.195	.197 (5)	.472	.071	.984	.236 - .394	68	120
F	48309	.195	.197 (5)	.354	.071	.650	.118 - .157	68	120
G	48330	.234	.236 (6.0)	.512	.098	1.102	.157 - .335	110	181
H	48349	.246	.250 (6.3)	.669	.098	.709	.157 - .236	121	194
I	48350	.246	.250 (6.3)	.669	.098	1.102	.157 - .394	121	194
J	48351	.246	.250 (6.3)	.512	.098	1.102	.157 - .394	121	194
K	48353	.246	.250 (6.3)	.670	.098	.682	.028 - .193	121	194
L	48354	.246	.250 (6.3)	.670	.098	.682	.028 - .178	121	194
M	48385	.258	.260 (6.6)	.512	.098	.787	.098 - .197	137	219
N	48386	.258	.260 (6.6)	.709	.098	.787	.098 - .197	137	219

* Also available in bulk 2,000/ctn and visual boxes, 20/pkg.

Plastic Rivets

Actual Size Rivets/Flanges When ordering, match diagram reference letter with those in above chart.



Plastic Rivet Tools



Klik-Lok™ Plastic Rivet Setter/48000

This plastic rivet setter delivers the extra-long pulling stroke needed to set plastic rivets. Its all-steel construction and full-size handles make for smooth easy operation. The tool is packaged in a reusable, heavy-duty vinyl pouch. Weight: .6 lb.



Klik-Lok™ Plastic Rivet Kit/48001

You'll be all set for the next job that requires plastic rivet fastening with this kit. The kit includes the 48000 Plastic Rivet Setter and a 20-pack each of our four most popular rivet sizes: No. 58106, 58108, 58149 and 58150. A reclosable carton provides storage for rivets and tool. Weight: 1.5 lbs.



Klik-Lok™ KL-2 Plastic Rivet Setter/48005

This long-reach tool is just what today's professional needs for hard-to-reach spots, especially in automotive applications such as flexible bumpers, wheel wells, license plate brackets and bumper reinforcements. In addition to the tool's long reach, it offers one-stroke setting and a universal nosepiece that sets all plastic rivets. The tool is packaged in a reusable, heavy-duty vinyl pouch. Weight: .75 lb.



Professional Plastic Rivet Kit/48006

This kit includes the versatile KL-2 Plastic Rivet Setter, plus a 20-pack each of our four most popular rivet sizes: No. 58106, 58108, 58149 and 58150. A reclosable carton provides storage for rivets and tool. Weight: 1.5 lbs.

Hand Rivet Tools

HP-2®/39000



The HP-2 is the largest selling hand rivet tool in the industry. Known and trusted for durability, quality and performance, the HP-2 is often copied but never equaled. Its square shoulder fulcrum pin of cold-formed heat-treated steel prevents pin rotation that can elongate the engaging holes and cause premature tool failure in imitation tools. Other quality features include: precision die-case, high-strength aluminum alloy body; drop-forged carbon steel upper handle; and thick, cushion-molded vinyl grips for comfort. The HP-2 sets up to $\frac{3}{16}$ " steel rivets and comes with four mounted nosepieces ($\frac{3}{32}$ ", $\frac{1}{8}$ ", $\frac{5}{32}$ " and $\frac{3}{16}$ ") and a service wrench. Refer to the Riveter Capacity Chart on page 19 for specific capabilities. Weight: 1.2lbs.



Klik-Turn™ SP-1/39005

The SP-1 swivel head hand-held rivet tool features a patented positive-ratchet locking feature which will allow the swivel head section of the tool to turn 360° and hold in place in any of the forty-plus positions. The high-strength steel body and cast aluminum head complement this new design in a swivel head riveting tool. The SP-1 also includes built-in threaded nosepiece storage holes and a service wrench. The SP-1 sets up to $\frac{3}{16}$ " steel rivets. Refer to the Riveter Capacity Chart on page 19 for specific capabilities. Weight: 1.2lbs.



200 Kit™/39001

The deluxe hand riveter kit includes the HP-2 and 200 assorted Klik-Fast rivets in popular sizes. The molded plastic case houses and protects the tool, rivets and optional countersink double ended drill bit. Weight: 4 lbs.

Stainless Steel Kit/39003

This kit is the same as our 39001, but contains 200 assorted Klik-Fast stainless steel rivets. Weight: 4 lbs.

The Kliker®/39040

The Kliker is a perfect medium-duty tool, setting all $\frac{1}{8}$ " to $\frac{5}{32}$ " steel, and $\frac{3}{16}$ " all aluminum Klik-Fast rivets. The Kliker comes packaged in a heavy-duty vinyl pouch with an assortment of Klik-Fast rivets and washers. Weight: 1 lb.



Hand Rivet Tools

Big Daddy®/39031

The Big Daddy is the most versatile and powerful Marson brand hand riveter, taking the hard work out of setting large diameter blind rivets. Its extra-long handles provide excellent leverage and permit working a foot beyond natural reach. Other features include a patented bearing design, self-adjusting two-piece jaws and single-unit body construction with a steel insert to provide stronger threads for the nosepieces included. In addition, the Big Daddy features a double-gear reduction system which easily sets from $\frac{1}{8}$ " to $\frac{1}{4}$ " diameter Klik-Fast rivets in all alloys, including $\frac{1}{4}$ " Klik-Split® and $\frac{3}{16}$ " and $\frac{1}{4}$ " Klik-Lok® rivets. And a one-piece collet case eliminates the need to adjust the tool when changing rivet diameters. The Big Daddy comes with $\frac{5}{32}$ ", $\frac{3}{16}$ " and $\frac{1}{4}$ " nosepieces which are stored in the body. Weight: 3.75 lbs.




Standard head



Big Daddy/39035

This is the same tool as 39010, but comes with 39009 attached, extending the tool's reach by an additional $2\frac{1}{2}$ ". Weight: 4 lbs.



Extended head



Big Daddy Extended Nosepiece Kit/39009

Just two installed parts extend the reach of 39031 or 39010 by an additional $2\frac{1}{2}$ ". Weight: .25 lb.

* When setting Marson brand Klik-Lok rivets, **no special nosepiece** is required.

Hand Rivet Tools

Hand Rivet Tool Capacity Chart

Riveter Model	Steel	All Aluminum	Aluminum/Steel	Stainless	Copper Steel	Klik-Lok®*	"T" Rivets
	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8" 5/32" 3/16" 1/4"	3/16" 1/4"	3/16" 1/4"
HP-2/39000	• • • •	• • • •	• • • •	• • • •	• • •	•	• •
SP-1/39005	• • • •	• • • •	• • • •	• • • •	• • •	•	• •
KR-II/39040	• • •	• • •	• • •	• • •	•	•	• •
BIG DADDY/39031	• • • •	• • • •	• • • •	• • • •	• • •	• • •	• • •

Hand Rivet Tools — Standard & Special Nosepieces

Tools	Sizes					Klik-Lok™ Sizes		T-Rivet Sizes	
	3/32"	1/8"	5/32"	3/16"	1/4"	3/16"	1/4"	3/16"	1/4"
39000	39131	39128	39130	39129					
39005	39160	39161	39162	39163					
39040	39131	39128	39130	39129					
39031		96024	96025	96026	96027	96031	96030	96029	96028

Air/Hydraulic Tools



39054/M-3

This heavy-duty air/hydraulic riveter with its newly designed **aluminum forged** head can hold up under demanding continuous use. The steel forged head allows for continuous full operating power and less internal wear. The M-3 will set blind rivets from $\frac{1}{8}$ " diameter in all alloys, up to $\frac{3}{16}$ ".

Included with the M-3 are standard $\frac{1}{8}$ ", $\frac{5}{32}$ ", and $\frac{3}{16}$ " nosepieces, a service wrench, swivel inlet air coupler and a mandrel collection bottle. The recommended airline pressure is 85-95 PSI. Weight: 4.2lbs.



39062/302-E

This durable riveter with its fully adjustable vacuum system holds the rivet in the nosepiece, allowing the operator to rivet at any angle with one hand free. The vacuum system also automatically collects the spent mandrel into a collection bottle. This creates a cleaner and safer work environment by preventing spent mandrels from falling to the floor or work surface. This tool can easily install $\frac{3}{32}$ " to $\frac{3}{16}$ " diameter rivets in all alloys, and $\frac{1}{4}$ " diameter open-end rivets in aluminum/steel combination. A swivel air inlet for increased mobility when working is also included along with a push button trigger and molded frame which provides the operator with maximum comfort using minimal effort. The recommended airline pressure is 85-95 PSI. Weight: 4 lbs.



39070/IL-1

This durable in-line riveter with its fully adjustable vacuum system holds the rivet in the nosepiece in any riveting position and automatically ejects the mandrel into an attached container (not supplied). The IL-1 is capable of setting rivet diameters from $\frac{3}{32}$ " through $\frac{3}{16}$ " in all alloys and easily hangs from any balancer. This is an ideal tool for assembly line riveting. The recommended airline pressure is 85-95 PSI. Weight: 3lbs.

39055/M-3V

The M-3V is capable of setting blind rivets from $\frac{3}{32}$ " diameter in all alloys up to $\frac{3}{16}$ ". Additionally, it has an internal vacuum system, which allows the mandrel to be held in position while operating the tool at any angle. After setting, the spent mandrel is ejected into the mandrel collection bottle. The recommended airline pressure is 85-95 PSI. Weight: 4.6lbs.



39064/304-E

This is our most powerful air/hydraulic riveter, with its fully enclosed vacuum system that holds the rivet in the nosepiece, allowing the operator to rivet at any angle with one hand free. The vacuum system automatically collects the spent mandrel into a bottle, creating a cleaner, safer work environment by preventing spent mandrels from falling to the floor. A traction pulling power of 4200 lbs. allows this tool to easily set Klik-Lok™ and all other structural blind rivets. Its long $\frac{7}{8}$ " stroke enables the tool to set most rivets in one pull. In addition to the nosepieces for structural rivets, nosepieces to install $\frac{3}{16}$ " and $\frac{1}{4}$ " standard rivets are also included along with a push button trigger and molded frame which provides the operator with maximum comfort using minimal effort. The recommended airline pressure is 85-95 PSI. Weight: 5.5 lbs.



39058/M-4

This heavy-duty air/hydraulic riveter with its newly designed **aluminum forged** head can hold up under demanding continuous use. The aluminum forged head allows for continuous full operating power and less internal wear. The M-4 can set rivets from $\frac{3}{32}$ " through $\frac{1}{4}$ " diameter in all alloys, and it also has the capability of setting $\frac{3}{16}$ " and $\frac{1}{4}$ " T-Rivets/Klik-Split™, Klik-Lok™ and all other structural blind rivets (*special optional nosepieces may be required*). The M-4 is supplied with $\frac{3}{32}$ ", $\frac{5}{32}$ ", $\frac{3}{16}$ " and $\frac{1}{4}$ " standard nosepieces, service tools, swivel inlet air coupler and a mandrel collection bottle. The recommended airline pressure is 85-95 PSI. Weight: 6.6 lbs.



**Extended head accessory
for 302-E and 304-E**

Tool	Description	Part Number
39062	5" Extension Head	88082
39062	8" Extension Head	88086
39064	5" Extension Head	88220-39

A balancer is available by special order for any of the above tools.

Air/Hydraulic Tools

Air/Hydraulic Rivet Tools — Standard & Special Nosepieces

Tool	Standard					T-Rivets/Klik-Split®		Structural*	
	3/32"	1/8"	5/32"	3/16"	1/4"	3/16"	1/4"	3/16"	1/4"
39054		95715	95716	95717					
39055	95761	95762	95763	95760					
39058	95897	95898	95899	95900	95835	95903	95905	95904	95906
39062	717006	717001	717002	717003	717005				
39064				88220-1	88220-79		88220-83	88220-85	88220-84
39070	717006	717001	717002	717003					

*For Monobolt® structural rivets, the noted special insert is required. For Marson brand Klick-Lock® structural rivets, no special insert is required.

Air/Hydraulic Rivet Tools — Capacity Chart


Riveter Model	Steel	All Aluminum	Aluminum/Steel	Stainless	Copper Steel	Structural	"T" Rivets
	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8" 5/32" 3/16" 1/4"	3/32" 1/8"	3/46" 1/4"	3/16" 1/4"
39054
39055
39058
39062
39064
39070

*For Monobolt® structural rivets, the noted special insert is required. For Marson brand Klick-Lock® structural rivets, no special insert is required.

Air/Hydraulic Tools


Air/Hydraulic Rivet Tools — Dimensions

Tool	A	B	C	D	E	F	G	WT
39054	12"	6"	1 1/4"	3"	6"	1"	3"	4.2 lbs.
39055	11.5"	9.5"	1.75"	3"	7"	.915"	4"	4.6 lbs.
39058	12"	4.5"	1.5"	3.5"	7"	.987"	4.5"	6.6 lbs.
39062	11.125"	5"	2.375"	4.5"	13"	.828"	2.5"	4 lbs.
39064	13.125"	6"	2.375"	5.25"	13"	.9375"	2.5"	5.5 lbs.
39070	15"	4"		3.125"	9"	.875"	2.5"	3 lbs.



Air/Hydraulic Rivet Tools — Specifications

Tool	Avg. Air		
	Work Force	Consumption	Stroke
39054	85-95 psi 1,983 lbs./8,820 n	4 cfm	.551" 14 mm
39055	85-95 psi 1,940 lbs./8,629 n	4 cfm	.551" 14 mm
39058	85-95 psi 3,099 lbs./13,784 n	5 cfm	.748" 19 mm
39062	85-95 psi 2,000 lbs./8,896 n	5 cfm	.812" 21 mm
39064	85-95 psi 4,200 lbs./18,682 n	5 cfm	.875" 22 mm
39070	85-95 psi 2,100 lbs./9341 n	4 cfm	.590" 15 mm



Threaded Insert Tools & Kits

Thread-Setter™ Tool/39200

This quality threaded insert installation tool features patented bearing design, comfortable hand grips and a locking chain. The 39200 installs all sizes of Klik Poly-Nuts and Klik Rivet-Nuts up to 1/4-20 and 6mm threads in steel. The forged, heat treated steel upper handle, precision die-cast body of high strength aluminum alloy, patented fulcrum pin design and comfortable hand grips all combine to make the 39200 a rugged, durable tool. The tool is packaged in a reusable, heavy-duty vinyl pouch containing mandrels and nosepieces to set 8-32, 10-24 and 10-32 inserts. Weight: 1.2 lbs.



Thread-Setter Kit/34501

Model 34501 Thread-Setter Kit contains the 39200 thread-setter tool in a molded plastic case; mandrels and nosepieces for 6-32, 8-32, 10-24 sizes, and a mandrel for 1/4-20. The kit also includes 103 assorted Klik Rivet-Nuts and Klik Poly-Nuts, instructions and wrench, all contained in a compartmentalized carrying case. Weight: 2.75 lbs.



Poly-Nut Kit/39202

Model 39202 Poly-Nut Kit contains the 39200 thread-setter tool in a molded plastic case with 8-32, 10-32 and 1/4-20 mandrels and nosepieces, wrench and instructions. The kit contains 52 assorted Klik Poly-Nuts: 12 each 57425, 57435, 57445; 16 each 57455. Weight: 3 lbs.



Metric Poly-Nut Kit/39203

Model 39203 Metric Poly-Nut Kit contains the 39200 thread-setter tool in a molded plastic case with 4mm, 5mm, 6mm and 8mm mandrels and nosepieces, wrench and instructions. The kit contains 75 assorted Klik Poly-Nuts: 25 each 57407, 57409; 15 each 57411; 10 each 57413. Weight: 3.25 lbs.



Ribbed Rivet-Nut Kit/39215

Model 39215 Ribbed Rivet-Nut kit contains the 39200 thread-setter tool in a molded plastic case; mandrels, nosepieces, wrench & instructions for setting 8-32, 10-24, 10-32 and 1/4-20 inserts. Includes 50 assorted Ribbed style Rivet-Nuts. Weight: 2.75 lbs.



Mandrel/Nosepiece Chart

For tool & kit Nos. 39200, 34501, 39202, 39203, 39213 and 39214

Thread Size	Mandrel No.	Nosepiece No.	Kit No.
6-32	39254	39261	39280
8-32	39255	39262	39281
10-24	39256	39263	39282
10-32	39257	39263	39283
1/4-20	39258	Not Needed	
5/16-18	39259	Not Needed	
3/8-16	39260	Not Needed	
4mm	39266	39274	39285
5mm	39267	39273	39286
6mm	39268	Not Needed	
8mm	39269	Not Needed	

Metric Ribbed Rivet-Nut Kit/39216

Model 39216 Ribbed Rivet-Nut kit contains the 39200 thread-setter tool in a molded plastic case with 4mm, 5mm, 6mm and 8mm mandrels and nosepieces, wrench and instructions. The kit also includes 50 assorted Ribbed style Rivet-Nuts. Weight: 2.75 lbs.



Steel Klik Thread-sert Kit/39214

Model 39214 Thread-sert Kit contains the 39200 thread-setter tool in a plastic case with 6-32, 8-32, 10-24, 10-32, 1/4-20, 5/16-18 and 3/8-16 mandrels and nosepieces, wrench and instructions. The kit contains 62 assorted Steel Klik Thread-serts: 10 each 57810, 57820, 57830, 57840, 57850; 6 each 57871, 57881. Weight: 3.25 lbs.



Aluminum Klik Thread-sert Kit/39213

Model 39213 Thread-sert Kit contains the 39200 thread-setter tool in a molded plastic case with 6-32, 8-32, 10-24, 10-32, 1/4-20, 5/16-18 and 3/8-16 mandrels and nosepieces, wrench and instructions. The kit contains 62 assorted Aluminum Klik Thread-serts: 10 each 57910, 57920, 57930, 57940, 57950; 6 each 57971, 57981. Weight: 3 lbs.



Threaded Insert Tools & Kits



34604/325RN

Choose the 34604 for installing larger size threaded inserts. Model 34604 is a heavy-duty tool that will install 10-24 through $\frac{3}{8}$ "-16, and 5mm through 10mm threaded inserts in aluminum or steel. Quick-change mandrels, easily adjustable stroke. Supplied with $\frac{1}{4}$ "-20 mandrel and nosepiece only. Weight: 4.25 lbs.

Mandrel/Nosepiece Chart

For 34604

Thread Size	Mandrel No.	Nosepiece No.	Kit No.
10-24	95635	95645	34615
10-32	95636	95645	34616
$\frac{1}{4}$ -20	95637	95647	34617
$\frac{5}{16}$ -18	95638	95648	34618
$\frac{3}{8}$ -16	95639	95649	34619
5mm	95630	95640	34625
6mm	95631	95641	34626
8mm	95632	95642	34627
10mm	95633	95643	34628



39221/150-SP

This spin-pull tool automatically threads the fastener onto the mandrel. Press the trigger and the fastener is installed. Reverse the trigger, and the mandrel spins out of the fastener.

The 39221 features a totally adjustable stroke length to suit any grip range and a swivel air inlet for increased mobility. No complicated tear down is required to adjust the stroke or to change thread sizes...both adjustments are done outside of the tool. The 39221 handles rivet-nut sizes 4-40 through $\frac{1}{2}$ "-20 and 3.5mm through 10mm in aluminum or steel. 6-32 through $\frac{3}{8}$ "-16 mandrels and nosepieces are included. Weight: 6 lbs.

Tool also available with metric mandrels and nosepieces, part No. 39222.



39223/140-SP

Similar to the 39221/150-SP, this lower cost alternative handles threaded insert sizes from 6-32 through $\frac{1}{4}$ "-20 and 4mm through 6mm in aluminum or steel. 6-32 through $\frac{1}{4}$ "-20 mandrels and nosepieces are included. Weight: 4.9 lbs.

Mandrel/Nosepiece Chart

For 39223


Thread Size	Mandrel No.	Nosepiece No.
6-32	88708	88701
8-32	88709	88702
10-24	88710	88703
10-32	88711	88703
$\frac{1}{4}$ -20	88712	88704
4mm	88651	88646
5mm	88652	88647
6mm	88653	88648

Mandrel/Nosepiece Chart

For 39221

Thread Size	Mandrel No.	Nosepiece No.
4-40	88187	88199
6-32	88188	88200
8-32	88189	88201
10-24	88191	88202
10-32	88190	88202
$\frac{1}{4}$ -20	88160	88161
$\frac{1}{4}$ -28	88192	88161
$\frac{5}{16}$ -18	88193	88203
$\frac{5}{16}$ -24	88194	88203
$\frac{3}{8}$ -16	88195	88204
$\frac{3}{8}$ -24	88196	88204
$\frac{1}{2}$ -13	88197	88205
$\frac{1}{2}$ -20	88198	88205
3.5mm	88206	88212
4mm	88207	88213
5mm	88208	88214
6mm	88209	88215
8mm	88210	88216
10mm	88211	88217

Klik® Rivet-Nuts



Cross section view

Available in Steel-Zinc Plated or Aluminum Class 2B Threads

Klik Rivet-Nuts (Flat Head)

Klik Rivet-Nuts can be used in a wide range of applications and are designed to provide a very efficient and cost-effective method of placing permanent threads in thin materials. Installed from one side, Klik Rivet-Nuts are perfect for use in metal, fiberglass and rigid plastic previously too thin for tapped threads. Klik Rivet-Nuts provide a neat appearance and once in place, the internal threads are ready for a screw or bolt.

Lightweight tooling assures easy installation by the operator and reduces costs when compared with other methods. After installation, Klik Rivet-Nuts provide permanent, captive threads that do not allow loosening under vibration and will not rotate when attached to the mating material.

Klik Rivet-Nuts with large diameter heads can be used in soft materials which inherently offer little, if any, thread strength.





The flathead design provides the most bearing surface for higher torque applications. The larger flange extends above the material in which it is installed and provides a built-in spacer.

Klik Rivet-Nut (Flat Head) Specifications


Thread Size	Steel Bulk Part #	Aluminum Bulk Part # ¹	A Body Length +.015"	B Head Dia. Ref. .015	C Head Height (MM) +.000-.004	D Body Dia. Max +.000-.004	Grip Range Min	Grip Range Max	Hole Size Min	Hole Size Max	Drill Size
6-32	57110	57210	.438	.325	.032	.189	.010	.075	.189	.193	# 12
8-32	57120	57220	.438	.357	.032	.221	.010	.075	.221	.226	# 2
8-32	57121	57221	.500	.357	.032	.221	.075	.120	.221	.226	# 2
10-24	57130	57230	.531	.406	.038	.250	.010	.080	.250	.254	1/4"
10-24	57132	57232	.594	.406	.038	.250	.080	.130	.250	.254	1/4"
10-32	57140	57240	.531	.406	.038	.250	.010	.080	.250	.254	1/4"
10-32	57142	57242	.594	.406	.038	.250	.080	.130	.250	.254	1/4"
1/4-20	57150	57250	.625	.475	.058	.332	.020	.080	.332	.338	Q
1/4-20	57152	57252	.687	.475	.058	.332	.080	.140	.332	.338	Q
1/4-20	57154	57254	.750	.475	.058	.332	.140	.200	.332	.338	Q
5/16-18	57171	57271	.750	.665	.062	.413	.030	.125	.413	.423	Z
5/16-18	57174	57274	.875	.665	.062	.413	.125	.200	.413	.423	Z
3/8-16	57181	57281	.844	.781	.088	.490	.030	.115	.490	.500	12.5mm
3/8-16	57184	57284	.938	.781	.088	.490	.115	.200	.490	.500	12.5mm

Rivet-Nut dimensions are in green indicating millimeters (mm).

4 Easy Steps for Installation



Klik® Poly-Nuts



Available in Steel-Zinc Plated or Aluminum Class 2B Threads

Klik Poly-Nuts (Expander)

Klik Poly-Nuts can be used in a wide range of applications and are designed to provide a very efficient and cost-effective method of placing permanent threads in thin materials. Installed from one side, Klik Poly-Nuts are perfect for use in metal, fiberglass and rigid plastic previously too thin for tapped threads. Klik Poly-Nuts provide a nearly flush appearance and once in place, the internal threads are ready for a screw or bolt.


Lightweight tooling assures easy installation by the operator and reduces costs when compared with other methods. After installation, Klik Poly-Nuts provide permanent, captive threads that do not allow loosening under vibration and will not rotate when attached to the mating material.

Klik Poly-Nut (Expander) Specifications

Thread Size	Steel	Aluminum	A Body Length +-.015"	B Head Dia. Ref. +-.015	D Body Dia. .005	Grip Range		Hole Size*		Drill Size
	Bulk Part#	Bulk Part #				Min	Max	Min	Max	
6-32	57415	57510	.410	.287	.249	.020	.080	.250	.254	1/4"
8-32	57425	57520	.410	.287	.249	.020	.080	.250	.254	1/4"
10-24	57435	57530	.465	.320	.280	.020	.130	.281	.285	9/32"
10-32	57445	57540	.465	.320	.280	.020	.130	.281	.285	9/32"
1/4-20	57455	57550	.610	.415	.374	.030	.165	.375	.379	3/8"
5/16-18	57475	57575	.720	.540	.499	.030	.165	.500	.504	1/2"
3/8-16	57485	57585	.720	.540	.499	.030	.165	.500	.504	1/2"
4 mm	57407		.410	.287	.249	.020	.080	.250	.254	1/4"
5 mm	57409		.465	.320	.280	.020	.130	.281	.285	9/32"
6 mm	57411		.610	.415	.374	.030	.165	.375	.379	3/8"
8 mm	57413		.720	.540	.499	.030	.165	.500	.504	1/2"
10 mm	57414		.720	.540	.499	.030	.165	.500	.504	1/2"

* Note: Hole size is critical for proper installation

Klik® Poly-Nuts



Klik® Thread-Serts

Thread-Serts

Klik Thread-Serts are a versatile threaded fastener that can be used in a variety of applications. Use Klik Thread-Serts in any thickness of metal or rigid material of at least $\frac{3}{32}$ " (.0937). Eliminate the need for tapping, welding and brazing. Klik Thread-Serts' design consists of an upper sleeve and a base which has both internal and external threads. During installation the base is drawn upwards inside the upper sleeve forcing a 360° contact between the sleeve and application material. No special preparation is needed; a drilled or punched hole is all that is required. Because of its unique setting ability, Klik Thread-Serts can be used in almost any thickness of material. Installation is made easy with a variety of tools and kits.

Thread-Sert Specifications

Thread Size	Steel Bulk Part #	Aluminum Bulk Part #	A* Body Length +.005"	B Head Dia. +.005	D* Body Dia. +.002"	Material Thickness .0937-.1562		Material Thickness .1562-Infinity	
						Hole Size	Drill Size	Hole Size	Drill Size
6-32	57810	57910	.375	.250	.215	0.221	#2	0.234	A
8-32	57820	57920	.375	.282	.246	0.250	1/4"	0.261	G
10-24	57830	57930	.375	.314	.277	0.281	9/32"	0.290	L
10-32	57840	57940	.375	.314	.277	0.281	9/32"	0.290	L
1/4-20	57850	57950	.510	.408	.372	0.391	25/64"	0.391	25/64"
5/16-18	57871	57971	.615	.537	.496	0.500	1/2"	0.516	33/64"
3/8-16	57881	57981	.740	.600	.559	0.562	9/16"	0.578	37/64"

* A and D dimensions are prior to setting


Klik® Rivet-Nuts/Ribbed

Steel Yellow Zinc Dichromate, Class 2B Threads

Klik Rivet-Nuts/Ribbed

Klik Rivet-Nuts/Ribbed can be used in a wide range of applications and are designed to provide a very efficient and cost-effective method of placing permanent threads in thin materials. Installed from one side, Klik Rivet-Nuts/Ribbed are perfect for use in metal, fiberglass and rigid plastic previously too thin for tapped threads. Klik Rivet-Nuts/Ribbed provide a neat appearance and once in place, the internal threads are ready for a screw or bolt. Additional features of the ribbed rivet-nut include: Increased torque strength over conventional style, 360° knurled expansion after setting, vibration resistance and large flanged head which increases push out strength. Available in steel only with yellow zinc dichromate finish and in a wide range of sizes: 6-32 thru 1/4-20, 5/16-18 and 3/8-16, M4 thru M10. Standard and extended grip ranges are available in each size.

Lightweight tooling assures easy installation by the operator and reduces costs when compared with other methods. After installation, Klik Rivet-Nuts/Ribbed provide permanent, captive threads that do not allow loosening under vibration and will not rotate when attached to the mating material. Klik Rivet-Nuts/Ribbed with large diameter heads can be used in soft materials which inherently offer little, if any thread strength. The flathead design provides the most bearing surface for higher torque applications. The larger flange extends above the material in which it is installed and provides a built-in spacer.



Klik Rivet-Nut/Ribbed Specifications

Thread Size	AFS Bulk Part#	A Body Length +.015" (mm)	B Head Dia. Ref. +.015 (mm)	C Head Height (NOM) (mm)	D Body Dia. Max +.000-.004 (mm)	Grip Range Min (mm)	Grip Range Max (mm)	Hole Size Required
6-32	57310	.433 10.9	.392 09.9	.028 .71	.264 06.7	.020 0.50	.080 2.03	17/64
6-32	57312	.484 12.3	.392 09.9	.028 .71	.264 06.7	.080 2.03	.130 3.30	17/64
8-32	57320	.433 10.9	.392 09.9	.028 .71	.264 06.7	.020 0.50	.080 2.03	17/64
8-32	57321	.484 12.3	.392 09.9	.028 .71	.264 06.7	.080 2.03	.130 3.30	17/64
10-24	57330	.488 12.3	.417 10.6	.028 .71	.295 07.5	.020 0.50	.130 3.30	19/64
10-24	57332	.594 15.0	.417 10.6	.028 .71	.295 07.5	.130 3.30	.225 5.71	19/64
10-32	57340	.488 12.3	.417 10.6	.028 .71	.295 07.5	.020 0.50	.130 3.30	19/64
10-32	57342	.594 15.0	.417 10.6	.028 .71	.295 07.5	.130 3.30	.225 5.71	19/64
1/4-20	57350	.590 14.9	.500 12.7	.028 .71	.390 09.9	.027 0.68	.165 4.19	25/64
1/4-20	57354	.692 17.5	.500 12.7	.028 .71	.390 09.9	.165 4.19	.260 6.60	25/64
5/16-18	57371	.690 17.5	.685 17.4	.032 .81	.530 13.5	.027 0.68	.150 3.81	17/32
5/16-18	57374	.805 20.4	.685 17.4	.032 .81	.530 13.5	.150 3.81	.312 7.92	17/32
3/8-16	57381	.690 17.5	.685 17.4	.032 .81	.530 13.5	.027 0.68	.150 3.81	17/32
3/8-16	57382	.805 20.4	.685 17.4	.032 .81	.530 13.5	.150 3.81	.312 7.92	17/32
M4	57360	.433 10.9	.392 09.9	.028 .71	.264 06.7	.020 0.50	.080 2.03	17/64
M4	57365	.484 12.3	.392 09.9	.028 .71	.264 06.7	.080 2.03	.130 3.30	17/64
M5	57385	.484 12.3	.417 10.5	.028 .71	.295 07.5	.020 0.50	.130 3.30	19/64
M5	57384	.594 15.0	.417 10.5	.028 .71	.295 07.5	.130 3.30	.225 5.71	19/64
M6	57386	.590 14.9	.500 12.7	.028 .71	.390 09.9	.027 0.68	.165 4.19	25/64
M6	57387	.692 17.5	.500 12.7	.028 .71	.390 09.9	.165 4.19	.260 6.60	25/64
M8	57388	.690 17.5	.685 17.4	.032 .81	.530 13.5	.027 0.68	.150 3.81	17/32
M8	57389	.805 20.4	.685 17.4	.032 .81	.530 13.5	.150 3.81	.312 7.92	17/32
M10	57390	.690 17.5	.685 17.4	.032 .81	.530 13.5	.027 0.68	.150 3.81	17/32
M10	57391	.805 20.4	.685 17.4	.032 .81	.530 13.5	.150 3.81	.312 7.92	17/32

Rivet-Nut dimensions are in green indicating millimeters (mm).

Conversion Tables

Inch-Metric Conversion Table

Inches			Inches		
Frac.	Dec.	mm	Frac.	Dec.	mm
1/64	0.015 625	0.3969	33/64	0.515 625	13.0969
1/32	0.031 250	0.7938	17/32	0.531 250	13.4938
3/64	0.046 875	1.1906	35/64	0.546 875	13.8906
1/16	0.062 500	1.5875	9/16	0.562 500	14.2875
5/64	0.078 125	1.9844	37/64	0.578 125	14.6844
3/32	0.093 750	2.3812	19/32	0.593 750	15.0812
7/64	0.109 375	2.7781	39/64	0.609 375	15.4781
1/8	0.125 000	3.1750	5/8	0.625 000	15.8750
9/64	0.140 625	3.5719	41/64	0.640 625	16.2719
5/32	0.156 250	3.9688	21/32	0.656 250	16.6688
11/64	0.171 875	4.3656	43/64	0.671 875	17.0656
3/16	0.187 500	4.7625	11/16	0.687 500	17.4625
13/64	0.203 125	5.1594	45/64	0.703 125	17.8594
7/32	0.218 750	5.5562	23/32	0.718 750	18.2562
15/64	0.234 375	5.9531	47/64	0.734 375	18.6531
1/4	0.250 000	6.3500	3/4	0.750 000	19.0500
17/64	0.265 625	6.7469	49/64	0.765 625	19.4469
9/32	0.281 250	7.1438	25/32	0.781 250	19.8437
19/64	0.296 875	7.5406	51/64	0.796 875	20.2406
5/16	0.312 500	7.9375	13/16	0.812 500	20.6375
21/64	0.328 125	8.3344	53/64	0.828 125	21.0344
11/32	0.343 750	8.7312	27/32	0.843 750	21.4312
23/64	0.359 375	9.1281	55/64	0.859 375	21.8281
3/8	0.375 000	9.5250	7/8	0.875 000	22.2250
25/64	0.390 625	9.9219	57/64	0.890 625	22.6219
13/32	0.406 250	10.3188	29/32	0.906 250	23.0188
27/64	0.421 875	10.7156	59/64	0.921 875	23.4156
7/16	0.437 500	11.1125	15/16	0.937 500	23.8125
29/64	0.453 125	11.5094	61/64	0.953 125	24.2094
15/32	0.468 750	11.9062	31/32	0.968 750	24.6062
31/64	0.484 375	12.3031	63/64	0.984 375	25.0031
1/2	0.500 000	12.7000	1	1.000 000	25.4000

Decimal Equivalents of Standard Sheet Gauges

Thickness in Thousandths		
No. of Gauge	Aluminum (B&S)	Steel (U.S. Std.)
10	.1019	.1345
11	.0907	.1196
12	.0808	.1046
13	.0720	.0897
14	.0641	.0747
15	.0571	.0673
16	.0508	.0598
17	.0453	.0538
18	.0403	.0478
19	.0359	.0418
20	.0320	.0359
21	.0285	.0329
22	.0253	.0299
23	.0226	.0269
24	.0201	.0239
25	.0179	.0209
26	.0159	.0179
27	.0142	.0164
28	.0126	.0149
29	.0113	.0135
30	.0100	.0120

Monobolt, Interlock and Hemlok are registered trademarks of Avdel Cherry Textron and Textron Inc. Ultra-Grip is a trademark of Emhart Fastening Technologies. Magna Lok and Magna Bulb are registered trademarks of Huck International. Tigerbolt is a registered trademark of Celus.



Along with a comprehensive selection of threaded inserts and riveting tools, Alcoa Fastening Systems (AFS) offers the broadest line of Marson® brand industrial and automotive blind fasteners available. AFS regularly makes nationwide delivery of product within hours when necessary. In addition to unsurpassed product coverage

and off-the-shelf availability, AFS provides such custom services as painting, plating, anodizing, packaging, bar-coding, and labeling for Marson products. The company's Total Quality Management System and QS-9000 certification reflects an uncompromising emphasis on quality assurance and customer satisfaction.

Alcoa Fastening Systems Commercial Products: A Global Organization

Alcoa Fastening Systems maintains company offices in the United States and Canada, with offices in many other countries. Authorized AFS distributors are also

located in many of the world's industrial centers, where they provide a ready source of fasteners, installation tools, tool parts, and application assistance.

Americas

Headquarters

8001 Imperial Drive
Waco, TX 76712, USA
P.O. Box 8117
Waco, TX 76714-8117, USA

Tel: 800 388 4825
Fax: 800 798 4825

Carmel Distribution
1051 Third Avenue SW
Carmel, IN 46032, USA
Tel: 800 732 3470 ext 1

Fax: 800 573 2645

Kingston Operations
1 Corporate Drive
Kingston, NY 12401, USA
Tel: 800 278 4825
Fax: 845 334 7333

Latin America Sales
Avenida Parque Lira
79-402 Tacubaya

MEXICO C P 11850
Tel: 52 55 5515 1776
Fax: 52 55 5277 7564

Mississauga Distribution
6150 Kennedy Road, Unit 10
Mississauga, Ontario L5T-2J4

CANADA

Tel: 905 564 4825
Fax: 905 564 1963

Stoughton Operations
44 Campanelli Parkway
Stoughton, MA 02072, USA
Tel: 800 732 3470 ext 2
Fax: 800 644 2177

Waco Operations
8001 Imperial Drive
Waco, TX 76712, USA
P.O. Box 8117
Waco, TX 76714-8117, USA
Tel: 800 388 4825
Fax: 800 798 4825

International Locations

Shanghai Sales
No.1277, Zhongshan Xi Road
Hailuo Building, Room 504
Shanghai, 200051, CHINA
Tel: 86-21-62700949
Fax: 86-21-62701964

Singapore Sales
Blk 194 Pandan Loop
#07-16 Pantech Industrial
Complex 128383, SINGAPORE

Melbourne Operations
20 Stamford Road
Oakleigh, Victoria, 3166

AUSTRALIA
Tel: 61 3 9567 3321
Fax: 61 3 9563 1980

Telford Operations
Unit C, Stafford Park 7
Telford, Shropshire TF3, 3BQ
UNITED KINGDOM
Tel: 44 1952 290011
Fax: 44 1952 290459

Your Authorized Distributor

The Future of Fastening Technology, The Future of Assembly Technology, The Future of Tooling Technology, and Tools of Productivity are service marks of Alcoa Fastening System. AFS provides technical assistance regarding the use and application of Huck fasteners and tooling.

B-AFS117 0804-00M

© 2004 Alcoa Fastening Systems

E-mail: AFS-Info@Alcoa.com • www.alcoafasteningsystems.com

NOTICE: The information contained in this publication is only for general guidance with regard to properties of the products shown and/or the means for selecting such products, and is not intended to create any warranty, express, implied, or statutory; all warranties are contained only in AFS's written quotations, acknowledgements, and/or purchase orders. It is recommended that the user secure specific, up-to-date data and information regarding each application and/or use of such products.

**Alcoa
Fastening
Systems**



One Great ConnectionSM